

MATERIAL SAFETY DATA SHEET

Section 1: Company Identification and Product information

Product Name: Purple Agar
Product Code No.: B696
Manufacturer's Name:
BIOMARK LABORATORIES
135/1, DALVI WADI, DHAIRI,
Pune - 411 041. INDIA
Tel. No. : (91)-8459755093,
E-mail: biomarklabs@gmail.com
Date of revision: December2022

Section 2: Composition/Information on Ingredients

This mixture is not classified as hazardous

Composition

Ingredients	grams/Litre
Peptone, special	10.00
Meat Extract B	1.00
Sodium chloride	5.00
Bromoss cresol purple	0.02
Agar	15.00

Section 3: Health Hazards Identification

Refer Section 2 and 15.

Section 4: First Aid Measures

General Information: No special measures required.

Ingestion: If swallowed, seek medical attention if symptoms occur. Show physician product label or MSDS.

Inhalation: If inhaled, supply fresh air or oxygen. Seek medical attention if breathing becomes labored or difficult

Eye Contact: Rinse opened eye for at least 15 minutes under running water, lifting lower and up eyelids occasionally. Seek medical attention.

Skin Contact: Remove contaminated clothing. Immediately wash with plenty of soap and water for at least 15 minutes. Wash clothing before reuse. Seek medical attention if irritation develops.

Section 5: Fire Fighting Measures

Use Carbon dioxide, ABC multipurpose dry chemical, or water spray. Fight larger fires with water spray or alcohol resistant foam. Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Section 6: Accidental Release Measures

Personal Precautions: Wear suitable protective clothing. Remove contaminated exhaustion at the workplace.

MATERIAL SAFETY DATA SHEET

Environmental Precautions: Prevent dispersion of material. Wipe up with damp sponge or mop.

Clean-up Methods: Avoid prolonged or repeated exposure. Absorb material, ventilate area, and wash spill site after material has been cleaned up. Avoid inhalation, contact with eyes and skin. Prevent formation of dust.

Section 7: Handling and Storage

Handling: Avoid inhaling dust. Avoid contact with eyes, skin and clothing. Refer to Section 8

Storage: Store in cool, dry conditions below 30°C in well-sealed containers and protected from direct sunlight and moisture.

Section 8: Exposure Controls/ Personal Protection

Wear appropriate NIOSH/MSHA-approved respirator, chemical-resistant gloves, safety goggles, other protective clothing. Mechanical exhaust required.

Section 9: Physical and Chemical Properties

Appearance: Homogeneous Free Flowing powder

Colour: Purplish cream

pH: 6.8 ± 0.2 at 25°C

Section 10: Stability and Reactivity

Stability: Stable under recommended storage and handling conditions

Conditions to avoid: Exposure to sunlight and moisture

Hazardous polymerization will not occur.

Section 11: Toxicological Information

LD/LC50 values that are relevant: N/A

Carcinogenicity: Not listed.

Section 12: Ecological Information

Eco toxicity Tests: No specific data available.

Section 13: Disposal Considerations

Disposal consideration: Non- hazardous waste. Dispose of according to all federal, state and local applicable regulations.

Container information: Containers should be cleaned by appropriate methods and then reused or disposed of by landfill or incineration as applicable.

Section 14: Transport Information

DOT Regulations: Not Regulated

Not classified.

MATERIAL SAFETY DATA SHEET

Section 15: Regulatory Information

Risk Phrases:

R 36/37/38, Irritating to eyes, respiratory system and skin.

Safety Phrases:

S 26, In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36, Wear suitable protective clothing.

Section 16: Other Information

Information contained herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty is expressed or implied regarding the completeness or accuracy of this information. Users of this material should satisfy themselves by independent investigation of current scientific or medical information that this material may be safely handled.